

SUBMARINE SINGLE CARCASS 19 bar 1000 Series**Type 1722S Mainline Hose With Location Collars**

Nominal Bore (mm)	Collar Outside Diameter (mm)				Weight in Air Empty (kg)			Minimum Bending Radius (m)
					Submerged Weight Full of Sea Water (kg)			
	D1	D2			9.1m	10.7m	12.2m	
	Body	End			(30ft)	(35ft)	(40ft)	
150 (6")	310	420	-	-	572 175	646 191	715 207	0.6
200 (8")	370	471	-	-	770 238	871 261	966 282	0.8
250 (10")	420	581	-	-	1027 334	1156 364	1279 392	1.0
300 (12")	471	581	-	-	1273 467	1439 512	1594 555	1.2
400 (16")	581	697	-	-	1776 689	2002 753	2214 814	1.6
500 (20")	697	799	-	-	2363 936	2668 1024	2954 1108	2.0
600 (24")	799	946	-	-	3082 1257	3484 1383	3862 1501	2.4

- Single Carcass Hose **perkenside** Mainline Standard Submarine Hose for use as the main submarine hose in the string to connect between sea bed manifold and buoy connection used on monobuoy systems
- Supplied with float location collars
- Rated Working Pressure: 19 bar
- Minimum Bending Radius: 4D (up to 2D without any permanent deformation)
- Electrical Continuity: Discontinuous or as requested