

FLOATING SINGLE CARCASS 19 bar 1000 Series**Type 1730F Reducer Hose**

Nominal Bore (mm)	Outside Diameter (mm)				Weight in Air Empty (kg)			Minimum Bending Radius (m)
	D1 End	D2 Body	D3 End		Weight in Air Full of Sea Water (kg)			
					9.1m (30ft)	10.7m (35ft)	12.2m (40ft)	
200/150 (8"/6")	410	365	400	-	587 756	666 865	741 967	0.9
250/200 (10"/8")	465	420	455	-	747 1043	846 1194	939 1336	1.2
250/150 (10"/6")	455	365	400	-	593 762	673 872	748 975	0.9
300/250 (12"/10")	560	505	550	-	1021 1475	1156 1690	1283 1892	1.5
300/200 (12"/8")	510	420	455	-	754 1050	854 1202	948 1345	1.2
300/150 (12"/6")	485	365	400	-	599 768	680 879	755 982	0.9
400/300 (16"/12")	635	570	620	-	1284 1953	1455 2241	1615 2511	1.8
400/250 (16"/10")	605	505	550	-	1031 1485	1162 1696	1296 1904	1.5
500/400 (20"/16")	790	725	775	-	1870 2956	2121 3398	2356 3812	2.4
500/300 (20"/12")	675	570	620	-	1291 1959	1462 2248	1623 2519	1.8
600/500 (24"/20")	925	860	910	-	2471 4194	2805 4831	3118 5428	3.0
600/400 (24"/16")	830	725	775	-	1879 2965	2132 3408	2368 3824	2.4

- Single Carcass Hose **perkenside** Reducer Bore for use to connect large mainline hose to smaller tail hose
- Rated Working Pressure: 19 bar
- Minimum Bending Radius: 6D (up to 2D without any permanent deformation)
- Minimum Reserve Buoyancy: 20% or as requested
- Electrical Continuity: Continuous or as requested